NSN 5930-00-230-2582

Hazardous Locations/environmental Protection:

Sensitive Switch - Page 1 of 2

Body Style:

Dustproof

1.000 inches **Bushing Length:**

0.500 inchesBody Length:1.937 inchesBody Width:0.687 inches

Bushing/hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-230-2582

Center To Center Distance Between Mounting Facilities Parallel To Length:

Body Height:
0.990 inches
Actuator Style:
Round
Actuator Diameter:
0.328 inches
Actuator Height:
0.339 inches
Actuator Free Position Height:
1.500 inches
Maximum Voltage Rating In Volts:
250.0 ac and 230.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 6.0 ounces and 10.0 ounces
Actuator Movement:
Between 0.040 pretravel inches and 0.219 overtravel inches and 0.003 differential inches
Thread Series Designator:
Uns

NSN 5930-00-230-2582

Sensitive Switch - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0