

View Online at <https://aerobasegroup.com/nsn/5930-00-230-7492>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.373 inches and 0.377 inches

**Body Length:**

Between 0.771 inches and 0.791 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.349 inches and 0.369 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.092 inches

**Actuator Height:**

0.110 inches

**Actuator Free Position Height:**

0.375 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.025 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Test Data Document:**

81349-mils8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/A

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0