## NSN 5930-00-230-8597

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-230-8597

| Hazardous Locations/environmental Protection:                                      |
|--|
| Weatherproof   |
| Housing Length:  |
| 4.050 inches   |
| Housing Width:   |
| 1.570 inches   |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length:  |
| 2.310 inches   |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width:   |
| 1.562 inches   |
| Maximum Voltage Rating In Volts:   |
| 240.0 ac and 230.0 dc  |
| Inclosure Type:  |
| Fully enclosed   |
| Features Provided:   |
| Actuator seal  |
| Nonpile-up Contact Arrangement:  |
| 1 two circuit, double break/double make, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:                              |
| 400.000 milliamperes resistive dc and 3.000 amperes resistive ac                   |
| Terminal Type And Quantity:  |
| 4 screw  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A053a0   |
|  |
|  |
|  |