NSN 5930-00-231-9774

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-231-9774

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Height:

1.852 inches

Overall Width:

1.852 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

3.438 inches single actuator

Nonturn Device Radius:

0.531 inches at 10: 30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 10: 30 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

120.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-231-9774

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Precious Material And Location: Contact clips silver and rotor blade silver Precious Material: Silver Style Designator: Circular wafer, bushing mount Thread Series Designator: Unef single mounting facility Shelf Life: N/a Unit Of Measure:

Demilitarization:

No Fiig: A052b0