NSN 5930-00-232-2240

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-232-2240

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Body Length:
0.789 inches
Body Width:
0.250 inches
Body Height:
0.480 inches
Unthreaded Mounting Hole Diameter:
0.090 inches
Actuator Length:
0.342 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.360 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
7.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 2.000 amperes inductive dc and 2.500 amperes resistive ac and 2.500 amperes inductive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-00-232-2240

Sensitive Switch - Page 2 of 2



Fiig:

A053a0