# NSN 5930-00-232-3227

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-232-3227

#### **Thread Class:**

2b all pressure connection

#### **Inside Diameter:**

0.438 inches all connections

#### **Overall Length:**

5.812 inches

#### **Overall Height:**

6.844 inches

#### **Overall Width:**

2.688 inches

**Body Length:** 

4.750 inches

Body Height:

2.750 inches

#### **Unthreaded Mounting Hole Diameter:**

0.281 inches

## Distance Between Mounting Facility Centers:

5.250 inches

Pressure Switch Type:

Differential

#### **Mounting Method:**

Bracket and unthreaded hole

### **Features Provided:**

Electrical access port

#### **Contact Action Stimulus:**

Increase

#### **Proof Pressure:**

160.00 pounds per square inch gage

#### **Thread Size:**

0.438 inches all pressure connection

#### Mounting Facility Pattern:

Two position in-line

#### Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

#### **Terminal Type:**

Screw

### **Contact Load Current Rating:**

9.6 amperes inductive load fifth voltage

#### **Contact Adjustability:**

Actuation point adjustable

#### **Contact Adjustment Range:**

+7.00/+70.00 actuation point pounds per square inch gage

# NSN 5930-00-232-3227

Pressure Switch - Page 2 of 2



Contact Adjustment Type: External actuation point screw **Contact Voltage Rating In Volts:** 550.0 dc at sea level eighth voltage Pressure Connector Type: Plain, threaded internal all connections Frequency In Hertz: 60.0 third voltage Media For Which Designed: Gas or gas, liquefied **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Rectangular **Thread Series Designator:** Unf all pressure connection Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig:

# A048b0

A048