## NSN 5930-00-232-6142

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-232-6142

Th	rea	h	lه	nc	nth	
	ıca	u	ᆫ	ıı۷	4411	

0.375 inches single mounting facility

#### First Flat Length:

0.375 inches single actuator

## Flat Height:

0.219 inches single actuator

## **Shaft Diameter:**

0.250 inches single actuator

#### **Shaft Length:**

0.938 inches single actuator

## **Individual Section Quantity:**

1

## **Switch Contact Basic Design:**

Nonpile-up symmetrical

#### **Pole Quantity:**

3 single section front

## **Throw Quantity:**

3 single section front

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

115.0 ac at sea level

## **Switch Actuator Indexing Position Quantity:**

3 single actuator

## **Shaft Type:**

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

## **Switch Actuator Positioning Increment:**

20.0 degrees single actuator

## **Switch Actuator Stop Device Type:**

Adjustable stop single actuator

## **Contact Load Current Rating:**

7.5 amperes resistive load ac at sea level

## **Thread Series Designator:**

Unef single mounting facility

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5930-00-232-6142

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0