

View Online at <https://aerobasegroup.com/nsn/5930-00-233-5065>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Body Length:**

Between 0.490 inches and 0.510 inches

**Body Width:**

Between 0.190 inches and 0.210 inches

**Body Height:**

Between 0.340 inches and 0.360 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.091 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.063 inches

**Actuator Height:**

0.095 inches

**Actuator Free Position Height:**

0.355 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 200.000 milliamperes lamp dc

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0