## NSN 5930-00-233-7305

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-233-7305

Thread Class:
2a single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.538 inches
Overall Height:
2.120 inches
Overall Width:
1.120 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
0.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear
Throw Quantity:
2 single section rear
Features Provided:
Features Provided:  Metallic inclosure
Metallic inclosure
Metallic inclosure Thready Qty Per Inch (tpi):
Metallic inclosure  Thready Qty Per Inch (tpi):  32 single mounting facility
Metallic inclosure  Thready Qty Per Inch (tpi):  32 single mounting facility  Thread Size:
Metallic inclosure  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.164 inches single mounting facility
Metallic inclosure  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Contact Voltage Rating In Volts:
Metallic inclosure  Thready Qty Per Inch (tpi):  32 single mounting facility  Thread Size:  0.164 inches single mounting facility  Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level
Metallic inclosure  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Mounting Facility Pattern:
Metallic inclosure  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility
Metallic inclosure  Thready Qty Per Inch (tpi):  32 single mounting facility  Thread Size:  0.164 inches single mounting facility  Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility  Switch Actuator Indexing Position Quantity:
Metallic inclosure  Thready Qty Per Inch (tpi):  32 single mounting facility  Thread Size:  0.164 inches single mounting facility  Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility  Switch Actuator Indexing Position Quantity:  3 single actuator
Metallic inclosure  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility  Switch Actuator Indexing Position Quantity: 3 single actuator  Shaft Type:
Metallic inclosure  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility  Switch Actuator Indexing Position Quantity: 3 single actuator  Shaft Type:  Round, flatted single actuator
Metallic inclosure Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round, flatted single actuator Terminal Type:
Metallic inclosure Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug
Metallic inclosure Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.164 inches single mounting facility Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Mounting Facility Pattern: Two position in-line single mounting facility Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Contact Switching Action:

Fixed stop single actuator

**Switch Actuator Stop Device Type:** 

## NSN 5930-00-233-7305

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

25.0 amperes resistive load highest ac voltage rating at sea level

**Style Designator:** 

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0