

View Online at <https://aerobasegroup.com/nsn/5930-00-233-9952>

**Width Between Flats:**

0.090 inches single actuator

**Overall Length:**

4.124 inches

**Overall Height:**

2.125 inches

**Overall Width:**

1.812 inches

**First Flat Length:**

0.156 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.875 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.187 inches single mounting facility

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

1.437 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.750 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

30.0 lowest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted w/through hole single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load lowest dc voltage rating at sea level and 2.0 amperes inductive load lowest dc voltage rating at sea level

**Special Features:**

Pin in through hole

**Precious Material And Location:**

Contacts and rotor blade surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0