

View Online at <https://aerobasegroup.com/nsn/5930-00-233-9952>

Width Between Flats:

0.090 inches single actuator

Overall Length:

4.124 inches

Overall Height:

2.125 inches

Overall Width:

1.812 inches

First Flat Length:

0.156 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.875 inches single actuator

Unthreaded Mounting Hole Diameter:

0.187 inches single mounting facility

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.750 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

30.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted w/through hole single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level and 2.0 amperes inductive load lowest dc voltage rating at sea level

Special Features:

Pin in through hole

Precious Material And Location:

Contacts and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0