

View Online at <https://aerobasegroup.com/nsn/5930-00-234-0431>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

Between 0.458 inches and 0.578 inches

Body Length:

0.659 inches

Body Width:

0.643 inches

Body Height:

1.380 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.246 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0