

View Online at <https://aerobasegroup.com/nsn/5930-00-234-0699>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Bushing Length:**

0.516 inches

**Body Length:**

1.938 inches

**Body Width:**

0.688 inches

**Body Height:**

0.891 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.328 inches

**Actuator Height:**

0.359 inches

**Actuator Free Position Height:**

1.558 inches

**Maximum Voltage Rating In Volts:**

460.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 6.0 ounces and 9.0 ounces

**Actuator Movement:**

Between 0.012 pretravel inches and 0.219 overtravel inches and 0.0005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0