

View Online at <https://aerobasegroup.com/nsn/5930-00-234-3428>

Thread Class:

3a single pressure connection

Overall Length:

2.000 inches

Overall Diameter:

0.900 inches

Pressure Switch Type:

Gage

Width Across Flats:

Between 0.684 inches and 0.692 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

1500.00 pounds per square inch

Thread Size:

0.4375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

3000.00 pounds per square inch

Terminal Type:

Wire lead

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

600.00 actuation point pounds per square inch gage and 150.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Special Features:

1.4 oz maximum wt excluding leads

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0