

View Online at <https://aerobasegroup.com/nsn/5930-00-234-3428>

**Thread Class:**

3a single pressure connection

**Overall Length:**

2.000 inches

**Overall Diameter:**

0.900 inches

**Pressure Switch Type:**

Gage

**Width Across Flats:**

Between 0.684 inches and 0.692 inches

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1500.00 pounds per square inch

**Thread Size:**

0.4375 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Sensing Element Burst Pressure:**

3000.00 pounds per square inch

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

4.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

600.00 actuation point pounds per square inch gage and 150.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Special Features:**

1.4 oz maximum wt excluding leads

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0