

View Online at <https://aerobasegroup.com/nsn/5930-00-234-3892>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus proof and shock resistant

Overall Length:

2.175 inches

Overall Height:

0.562 inches

Overall Width:

0.562 inches

Body Diameter:

0.562 inches

Bushing Length:

0.425 inches

Body Length:

1.040 inches

Case Material:

Metal

Actuator Length:

0.500 inches

Actuator Style:

Rectangular

Actuator Height:

0.505 inches

Actuator Width:

0.500 inches

Actuator Color:

Red single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 7.000 amperes resistive ac and 3.000 amperes inductive ac

Precious Material And Location:

Contact surfaces gold and contacts silver

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0