

View Online at <https://aerobasegroup.com/nsn/5930-00-234-9197>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

1.125 inches

**Overall Height:**

2.204 inches

**Overall Width:**

0.625 inches

**Bushing Length:**

0.469 inches

**Body Length:**

1.125 inches

**Body Width:**

0.625 inches

**Actuator Style:**

Round

**Actuator Height:**

0.688 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

440.0 ac and 30.0 dc

**Mounting Surface To Terminal End Distance:**

1.047 inches

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc and 20.000 amperes motor dc and 3.000 amperes resistive ac and 3.000 amperes inductive ac and 2.200 amperes motor ac

**Precious Material And Location:**

Contacts silver

**Test Data Document:**

11243-c3200708-3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0