

View Online at <https://aerobasegroup.com/nsn/5930-00-234-9197>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.125 inches

Overall Height:

2.204 inches

Overall Width:

0.625 inches

Bushing Length:

0.469 inches

Body Length:

1.125 inches

Body Width:

0.625 inches

Actuator Style:

Round

Actuator Height:

0.688 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

440.0 ac and 30.0 dc

Mounting Surface To Terminal End Distance:

1.047 inches

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc and 20.000 amperes motor dc and 3.000 amperes resistive ac and 3.000 amperes inductive ac and 2.200 amperes motor ac

Precious Material And Location:

Contacts silver

Test Data Document:

11243-c3200708-3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0