NSN 5930-00-235-3227

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-235-3227

Thread Class:
2a
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
0.815 inches
Overall Height:
2.480 inches
Overall Width:
0.656 inches
Bushing Length:
0.950 inches
Body Length:
0.780 inches
Body Width:
0.656 inches
Body Height:
0.850 inches
Case Material:
Case Material: Plastic
Plastic
Plastic Actuator Diameter:
Plastic Actuator Diameter: 0.750 inches
Plastic Actuator Diameter: 0.750 inches Actuator Height:
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color:
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts:
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type:
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method:
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided:
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Actuator seal
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Actuator seal Thready Qty Per Inch (tpi):
Plastic Actuator Diameter: 0.750 inches Actuator Height: 0.490 inches Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed Mounting Method: Threaded bushing Features Provided: Actuator seal Thready Qty Per Inch (tpi): 32

2 pole, double throw, one position momentary single switch unit

NSN 5930-00-235-3227

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0