## NSN 5930-00-235-5674

Thermostatic Switch - Page 1 of 2

Gas or liquid



View Online at https://aerobasegroup.com/nsn/5930-00-235-5674

Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
3.375 inches
Overall Height:
5.875 inches
Overall Width:
3.125 inches
Capillary Tube Length:
84.0 inches
Bulb Length:
10.000 inches
Bulb Diameter:
0.188 inches
End Application:
Heater-turb rotor 77445
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Base
Features Provided:
Pilot light
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
35.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+150.00/+550.00 actuation point degrees fahrenheit and +150.00/+550.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point knob with scale and external actuation point knob with scale
Contact Voltage Rating In Volts:
277.0 ac at sea level first voltage
Frequency In Hertz:
60.0 second voltage
Media For Which Designed:

## NSN 5930-00-235-5674

Thermostatic Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0