

View Online at <https://aerobasegroup.com/nsn/5930-00-235-5674>

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

3.375 inches

Overall Height:

5.875 inches

Overall Width:

3.125 inches

Capillary Tube Length:

84.0 inches

Bulb Length:

10.000 inches

Bulb Diameter:

0.188 inches

End Application:

Heater-turb rotor 77445

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Base

Features Provided:

Pilot light

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

35.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+150.00/+550.00 actuation point degrees fahrenheit and +150.00/+550.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

277.0 ac at sea level first voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0