

View Online at <https://aerobasegroup.com/nsn/5930-00-235-9418>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.310 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.020 inches

**Overall Height:**

1.120 inches

**Overall Width:**

0.900 inches

**First Flat Length:**

0.520 inches single actuator

**Flat Height:**

0.093 inches single actuator

**Shaft Diameter:**

0.125 inches single actuator

**Shaft Length:**

0.780 inches single actuator

**Nonturn Device Radius:**

0.250 inches at 6: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Key at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 ac at sea level

**Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, one position momentary single switch single section rear

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Special Features:**

Flexible insulators

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0