

View Online at <https://aerobasegroup.com/nsn/5930-00-235-9418>

Thread Class:

2a single mounting facility

Thread Length:

0.310 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.020 inches

Overall Height:

1.120 inches

Overall Width:

0.900 inches

First Flat Length:

0.520 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.780 inches single actuator

Nonturn Device Radius:

0.250 inches at 6: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Key at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary single switch single section rear

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Special Features:

Flexible insulators

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0