## NSN 5930-00-235-9729

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-235-9729

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 4.500 inches **Overall Height:** 1.875 inches **Overall Width:** 1.625 inches First Flat Length: 0.375 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.500 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 6 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-235-9729

Rotary Switch - Page 2 of 2



## **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 500.0 milliamperes resistive load ac at sea level **Precious Material And Location:** Contacts and rotor blade surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0