NSN 5930-00-236-2124

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-236-2124

Thread Class: 2a single mounting facility Thread Length: 0.313 inches single mounting facility **Overall Length:** 1.801 inches **Overall Height:** 1.250 inches **Overall Width:** 1.260 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.750 inches single actuator **Nonturn Device Radius:** 0.375 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 3: 00 o'clock **Operating Tempurature Range:** -40.0/+89.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 2 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

NSN 5930-00-236-2124

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0