

View Online at <https://aerobasegroup.com/nsn/5930-00-236-2129>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.380 inches single mounting facility

**Overall Length:**

2.780 inches

**First Flat Length:**

0.380 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.880 inches single actuator

**Overall Diameter:**

1.540 inches

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

195.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0