

View Online at <https://aerobasegroup.com/nsn/5930-00-236-2218>

Inside Diameter:

0.250 inches all connections

Hazardous Locations/environmental Protection:

Corrosion resistant and dustproof and vibration resistant and watertight

Overall Length:

8.080 inches

Overall Height:

2.688 inches

Overall Width:

4.750 inches

Body Length:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

1.906 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

90.00 pounds per square inch

Thread Size:

0.250 inches all pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+90.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut

Contact Stimulus Rating:

35.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0