

View Online at <https://aerobasegroup.com/nsn/5930-00-236-2220>

**Thread Class:**

2b all pressure connection

**Overall Length:**

7.624 inches

**Overall Height:**

2.656 inches

**Body Length:**

3.000 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.219 inches

**Longest Vertical Distance Between Mounting Centers:**

1.875 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Connector, plug

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.00/+90.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

0.87 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

250.0 ac at sea level first voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0