

View Online at <https://aerobasegroup.com/nsn/5930-00-236-2220>

Thread Class:

2b all pressure connection

Overall Length:

7.624 inches

Overall Height:

2.656 inches

Body Length:

3.000 inches

Longest Horizontal Distance Between Mounting Centers:

4.219 inches

Longest Vertical Distance Between Mounting Centers:

1.875 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, plug

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable

Contact Adjustment Range:

+0.00/+90.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

0.87 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0