

View Online at <https://aerobasegroup.com/nsn/5930-00-236-4809>

**Thread Class:**

3a single threaded bushing

**Thread Length:**

0.350 inches single threaded bushing

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

Between 4.030 inches and 4.230 inches

**Body Diameter:**

0.380 inches

**Body Length:**

Between 2.030 inches and 2.230 inches

**Bulb Length:**

1.400 inches

**Bulb Diameter:**

0.380 inches

**Temperature Sensing Element Type:**

Bulb

**Width Across Flats:**

0.750 inches

**Operating Temperature Rating:**

50.0 degrees celsius and -10.0 degrees celsius

**Mounting Method:**

Threaded bushing

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

20 single threaded bushing

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

170.00 actuation point degrees fahrenheit and 150.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical w/flange

**Thread Series Designator:**

Unf single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0