

View Online at <https://aerobasegroup.com/nsn/5930-00-236-4810>

Thread Class:

3a single threaded bushing

Thread Length:

0.350 inches single threaded bushing

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

Between 4.280 inches and 4.480 inches

Body Diameter:

0.380 inches

Body Length:

Between 2.030 inches and 2.230 inches

Bulb Length:

1.400 inches

Bulb Diameter:

0.380 inches

Temperature Sensing Element Type:

Bulb

Width Across Flats:

0.750 inches

Operating Temperature Rating:

50.0 degrees celsius and -10.0 degrees celsius

Mounting Method:

Threaded bushing

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

20 single threaded bushing

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

230.00 actuation point degrees fahrenheit and 200.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0