NSN 5930-00-236-4814

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-236-4814

Thread Class: 3a single pressure connection **Thread Length:** 0.550 inches single pressure connection **Overall Length:** 2.750 inches **Outside Diameter:** 0.438 inches single connection **Body Length:** 1.650 inches **Overall Diameter:** 0.750 inches **Pressure Switch Type:** Gage Width Across Flats: 0.750 inches **Operating Tempurature Rating:** Between -34.0 degrees celsius and 74.0 degrees celsius **Mounting Method:** Line **Contact Action Stimulus:** Increase **Proof Pressure:** 1500.00 pounds per square inch gage **Thread Size:** 0.438 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 2.0 amperes resistive load single voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 125.00 actuation point pounds per square inch gage and 75.00 deactuation point pounds per square inch gage **Contact Voltage Rating In Volts:** 28.0 dc at sea level single voltage **Pressure Connector Type:** Flared, threaded external single connection

Liquid

Media For Which Designed:

NSN 5930-00-236-4814

Pressure Switch - Page 2 of 2



or:
or

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0