## NSN 5930-00-236-5996

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-236-5996

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.829 inches **Overall Height:** 1.312 inches **Overall Width:** 1.125 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.875 inches single actuator **Nonturn Device Radius:** 0.531 inches at 9: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 single section front **Throw Quantity:** 3 single section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

250.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Shaft Type:** 

Round, hollowed single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Makes before breaks single section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-236-5996

Rotary Switch - Page 2 of 2



## **Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:** 

750.0 milliamperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0