

View Online at <https://aerobasegroup.com/nsn/5930-00-236-6025>

Thread Class:

2b

Body Style:

Hole mounted

Overall Length:

1.460 inches

Overall Height:

1.795 inches

Overall Width:

0.520 inches

Body Length:

1.340 inches

Body Width:

0.520 inches

Body Height:

1.300 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.495 inches and 0.505 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

0.455 inches

Actuator Free Position Height:

0.455 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

64.0 ounces

Actuator Movement:

0.130 pretravel inches and 0.250 overtravel inches and 0.155 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0