NSN 5930-00-236-6025

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-236-6025 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 1.460 inches **Overall Height:** 1.795 inches **Overall Width:** 0.520 inches **Body Length:** 1.340 inches **Body Width:** 0.520 inches **Body Height:** 1.300 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** Between 0.495 inches and 0.505 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.245 inches and 0.255 inches **Actuator Height:** 0.455 inches **Actuator Free Position Height:** 0.455 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:**

4.0 ounces

Switch Actuating Force:

64.0 ounces

NSN 5930-00-236-6025

Sensitive Switch - Page 2 of 2



Actuator Movement:

0.130 pretravel inches and 0.250 overtravel inches and 0.155 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0