

View Online at <https://aerobasegroup.com/nsn/5930-00-236-8037>

Body Style:

Hole mounted

Overall Length:

0.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

Overall Height:

0.480 inches

Overall Width:

0.200 inches

Body Length:

0.500 inches

Body Width:

0.200 inches

Body Height:

0.350 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.087 inches

Actuator Style:

Round

Actuator Diameter:

0.063 inches

Actuator Height:

0.030 inches

Actuator Free Position Height:

0.320 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.001 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 2.000 amperes inductive dc and 7.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0