NSN 5930-00-236-8037

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-236-8037

Hole mounted
Overall Length:
0.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.188 inches
Overall Height:
0.480 inches
Overall Width:
0.200 inches
Body Length:
0.500 inches
Body Width:
0.200 inches
Body Height:
0.350 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.087 inches
Actuator Style:
Round
Actuator Diameter:
0.063 inches
Actuator Height:
0.030 inches
Actuator Free Position Height:
0.320 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.001 differential inches

NSN 5930-00-236-8037

Sensitive Switch - Page 2 of 2



	Contact Load	Current Ra	ating At	Maximum	Rated V	oltage:
--	--------------	-------------------	----------	---------	---------	---------

3.000 amperes resistive dc and 2.000 amperes inductive dc and 7.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0