## NSN 5930-00-236-8037

Sensitive Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-00-236-8037

Hole mounted					
Overall Length:					
0.500 inches					
Center To Center Distance Between Mounting Facilities Parallel To Length:					
0.188 inches					
Overall Height:					
0.480 inches					
Overall Width:					
0.200 inches					
Body Length:					
0.500 inches					
Body Width:					
0.200 inches					
Body Height:					
0.350 inches					
Case Material:					
Plastic					
Unthreaded Mounting Hole Diameter:					
0.087 inches					
Actuator Style:					
Round					
Actuator Diameter:					
0.063 inches					
Actuator Height:					
0.030 inches					
Actuator Free Position Height:					
0.320 inches					
Maximum Voltage Rating In Volts:					
250.0 ac and 28.0 dc					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Unthreaded hole					
Nonpile-up Contact Arrangement:					
1 pole, double throw, one position momentary single switch unit					

Switch Release Force:

1.0 ounces

**Switch Actuating Force:** 

5.0 ounces

**Actuator Movement:** 

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.001 differential inches

## NSN 5930-00-236-8037

Sensitive Switch - Page 2 of 2



	Contact Load	<b>Current Rat</b>	ing At Ma	ximum Rat	ed Voltage:
--	--------------	--------------------	-----------	-----------	-------------

3.000 amperes resistive dc and 2.000 amperes inductive dc and 7.000 amperes resistive ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

3 turret

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0