## NSN 5930-00-236-8042

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-236-8042

**Thread Class:** 2b single mounting facility **Overall Length:** 2.593 inches **Overall Height:** 2.766 inches **Overall Width:** 2.766 inches **Shaft Diameter:** 0.248 inches single actuator and 0.251 inches single actuator **Shaft Length:** 0.906 inches single actuator and 0.968 inches single actuator **Individual Section Quantity:** 1 **Longest Horizontal Distance Between Mounting Centers:** 1.495 inches single mounting facility and 1.505 inches single mounting facility **Operating Tempurature Range:** -65.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 8 single section rear **Throw Quantity:** 2 single section rear **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator **Terminal Type:** 

Turret

**Contact Switching Action:** 

Breaks before makes single section front

## **NSN 5930-00-236-8042**Rotary Switch - Page 2 of 2

Fiig: A052b0



Switch Actuator Positioning Increment:
30.0 degrees single actuator
Detent Rotational Torque Range:
+2.000/+13.000 inch-pounds single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
1.0 amperes resistive load dc at sea level
Style Designator:
Tap, square frame
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No