NSN 5930-00-237-7403

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-237-7403

| Body Style: |
|---|
| Bushing/hole mounted |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Bushing Length: |
| 0.500 inches |
| Body Length: |
| 1.937 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 0.990 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.328 inches |
| Actuator Height: |
| 0.339 inches |
| Actuator Free Position Height: |
| 1.500 inches |
| Actuator Adapter Style: |
| Pushbutton |
| Center To Center Distance Between Adapter Mounting Facilities Parallel To Length: |
| 1.812 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 230.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Features Provided: |
| Actuator seal |
| Thread Size: |
| 0.138 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| 16.0 ounces |
| Actuator Movement: |

Actuator Movement.

Between 0.187 pretravel inches and 0.093 overtravel inches and 0.005 differential inches

NSN 5930-00-237-7403

Sensitive Switch - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Unf |
| Terminal Type And Quantity: |
| 2 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0