NSN 5930-00-237-7425

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted

1.000 inchesOverall Height:1.500 inchesOverall Width:



View Online at https://aerobasegroup.com/nsn/5930-00-237-7425

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.828 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
1.812 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.250 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.156 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
5.0 ounces
Switch Actuating Force:
3.0 ounces
Actuator Movement:
Between 0.156 pretravel inches and 0.062 overtravel inches and 0.030 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
2 tab, solder lug

NSN 5930-00-237-7425

Sensitive Switch - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0