

View Online at <https://aerobasegroup.com/nsn/5930-00-238-0283>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Watertight

Body Diameter:

0.625 inches

Bushing Length:

0.310 inches

Maximum Voltage Rating In Volts:

125.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0