NSN 5930-00-238-2432

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-238-2432

Overall Length:
8.625 inches
Overall Height:
4.750 inches
Overall Width:
4.750 inches
First Flat Length:
1.125 inches single actuator
Flat Height:
0.281 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.563 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility and 0.410 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Longest Horizontal Distance Between Mounting Centers:
3.781 inches single mounting facility
3.781 inches single mounting facility
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers:
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design:
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity:
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front Throw Quantity:
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front Throw Quantity: 2 each section rear
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front Throw Quantity: 2 each section rear Mounting Method:
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front Throw Quantity: 2 each section rear Mounting Method: Unthreaded hole single mounting facility
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front Throw Quantity: 2 each section rear Mounting Method: Unthreaded hole single mounting facility Features Provided:
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front Throw Quantity: 2 each section rear Mounting Method: Unthreaded hole single mounting facility Features Provided: Actuator knob
3.781 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 3.781 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical Pole Quantity: 1 each section front Throw Quantity: 2 each section rear Mounting Method: Unthreaded hole single mounting facility Features Provided: Actuator knob Contact Voltage Rating In Volts:

Mounting Facility Pattern:

Four position rectangular single mounting facility

NSN 5930-00-238-2432Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, flatted, threaded hole single actuator
Terminal Type:
Threaded stud
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
60.0 amperes resistive load ac at sea level
Style Designator:
Tap, square frame
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0