## NSN 5930-00-238-2577

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-238-2577 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length: 4.437** inches **Overall Height:** 1.188 inches **Overall Width:** 0.875 inches **Bushing Length:** 0.422 inches **Body Width:** 0.875 inches **Body Height:** 1.188 inches **Actuator Style:** Round **Actuator Height:** 0.984 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position maintained **Actuator Position-locking Relationship:** Up position no locking action and down position no locking action and center position locked in **Maximum Voltage Rating In Volts:** 120.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): **Pile-up Contact Form Arrangement:** 3c 2nd position **Thread Size:** 0.469 inches **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes resistive ac **Precious Material And Location:** 

Uns

Contacts palladium

**Thread Series Designator:** 

## NSN 5930-00-238-2577

Lever Switch - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0