## NSN 5930-00-238-2851

Rotary Switch - Page 1 of 2



| Rolary Switch - Page 1 of 2                                   |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-00-238-2851 |
| Thread Class:   |
| 2a single mounting facility                                   |
| Thread Length:  |
| 0.375 inches single mounting facility                         |
| Overall Length:   |
| 3.097 inches  |
| Overall Height:   |
| 0.968 inches  |
| Overall Width:  |
| 0.937 inches  |
| Shaft Diameter:   |
| 0.247 inches single actuator and 0.250 inches single actuator |
| Shaft Length:   |
| 1.875 inches single actuator                                  |
| Nonturn Device Radius:  |
| 0.375 inches at 9: 00 o'clock                                 |
| Individual Section Quantity:                                  |
| 3   |
| Nonturn Device Type:  |
| Tab at 9: 00 o'clock  |
| Switch Contact Basic Design:                                  |
| Nonpile-up symmetrical  |
| Pole Quantity:  |
| 1 each section rear   |
| Throw Quantity:   |
| 6 each section rear   |
| Mounting Method:  |
| Threaded bushing single mounting facility                     |
| Thread Size:  |
| 0.375 inches single mounting facility                         |
| Contact Voltage Rating In Volts:                              |
|   |

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

Shaft Type:

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

## NSN 5930-00-238-2851

Rotary Switch - Page 2 of 2



## **Switch Actuator Stop Device Type:**

Fixed stop single actuator

## **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0