

View Online at <https://aerobasegroup.com/nsn/5930-00-238-2997>

**Thread Class:**

2b all pressure connection

**Thread Length:**

0.500 inches single threaded bushing

**Overall Length:**

3.750 inches

**Overall Diameter:**

4.062 inches

**Pressure Switch Type:**

Absolute

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32 single threaded bushing

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.500 inches single threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

100.0 milliamperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point adjustable, preset

**Contact Adjustment Range:**

+3.00/+10.00 actuation point inches of water

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

14.00 actuation point inches of water and 14.00 deactuation point inches of water and 4.00 differential point inches of water

**Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Liquid

**Precious Material And Location:**

Contacts gold

**Precious Material:**

Gold

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Un single threaded bushing

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0