NSN 5930-00-239-0072

Rotary Switch - Page 1 of 2

0.375 inches single mounting facility

Thread Length:

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-00-239-0072

2.625 inches
Overall Height:
1.875 inches
Overall Width:
1.625 inches
First Flat Length:
0.375 inches single actuator
Flat Height:
0.219 inches single actuator
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.875 inches single actuator
Individual Section Quantity:
2
Nonturn Device Type:
Tab at 9: 00 o'clock
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
Pole Quantity: 4 each section rear
•
4 each section rear
4 each section rear Throw Quantity:
4 each section rear Throw Quantity: 2 each section rear
4 each section rear Throw Quantity: 2 each section rear Mounting Method:
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size:
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity:
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type:
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type:
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Contact Switching Action:
4 each section rear Throw Quantity: 2 each section rear Mounting Method: Threaded bushing single mounting facility Thread Size: 0.375 inches single mounting facility Switch Actuator Indexing Position Quantity: 2 single actuator Shaft Type: Round, flatted single actuator Terminal Type: Tab, solder lug Contact Switching Action: Breaks before makes each section rear

Circular wafer, bushing mount

NSN 5930-00-239-0072

Rotary Switch - Page 2 of 2



Thread Series Designato	TI	nread	Series	Design	ator
-------------------------	----	-------	--------	--------	------

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0