NSN 5930-00-240-0264

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-240-0264

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 4.063 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.438 inches |
| Overall Height: |
| 1.312 inches |
| Overall Width: |
| 0.625 inches |
| Body Width: |
| 0.625 inches |
| Body Height: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.000 inches |
| Actuator Style: |
| Round |
| Actuator Height: |
| 1.188 inches |
| Actuator Position-action Relationship: |
| Up position momentary and down position maintained |
| Actuator Position-locking Relationship: |
| Up position no locking action and down position locked in and out |
| Maximum Voltage Rating In Volts: |
| 110.0 ac |
| Inclosure Type: |
| Uninclosed |
| Thready Qty Per Inch (tpi): |
| 40 |
| Pile-up Contact Form Arrangement: |
| 2a 2nd position |
| Thread Size: |
| 0.112 inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes resistive ac |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 8 tab, solder lug |

N/a

Shelf Life:

NSN 5930-00-240-0264

Lever Switch - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A053a0