## NSN 5930-00-240-2714

Thermostatic Switch - Page 1 of 2

Cylindrical w/flange



View Online at https://aerobasegroup.com/nsn/5930-00-240-2714

Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
5.266 inches
Body Diameter:
0.625 inches
Body Length:
3.281 inches
Overall Diameter:
3.750 inches
Tempurature Sensing Element Type:
Immersion well
Operating Tempurature Rating:
Between -100.0 degrees fahrenheit and 225.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Features Provided:
Tamper proof cap
Thready Qty Per Inch (tpi):
14 single threaded bushing
Contact Action Stimulus:
Increase
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+25.00/+225.00 actuation point degrees fahrenheit and +25.00/+225.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
Internal deactuation point screw and internal actuation point screw
Contact Voltage Rating In Volts:
250.0 ac at sea level single voltage
Media For Which Designed:
Gas or liquid
Style Designator:

## NSN 5930-00-240-2714

Thermostatic Switch - Page 2 of 2



Ī	hread	<b>Series</b>	Designato	r:

Npt single threaded bushing

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0