NSN 5930-00-240-4149

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-240-4149 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** Between 0.998 inches and 1.002 inches Overall Width: 0.688 inches **Body Length:** 1.938 inches **Body Width:** 0.688 inches **Body Height:** 0.797 inches **Unthreaded Mounting Hole Diameter:** Between 0.139 inches and 0.142 inches **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.406 inches **Actuator Roller Diameter:** 0.375 inches **Actuator Roller Width:** 0.156 inches **Maximum Voltage Rating In Volts:** 460.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action single switch unit **Switch Release Force:** 0.7 ounces **Switch Actuating Force:** Between 1.0 ounces and 3.5 ounces **Contact Load Current Rating At Maximum Rated Voltage:** 250.000 milliamperes resistive dc and 15.000 amperes resistive ac **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5930-00-240-4149 Sensitive Switch - Page 2 of 2



Fiig:

A053a0